Interface® San Roco



Installation Method







Quarter turn

Brick

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see

www.interface.com/disclaimer.

Product San Roco Color 8870 Bruna Collection Pietra Backing GlasBac®

Product Specifications		
Product Number	1466802500	
Product Construction	Tufted Textured Loop	
Yarn System	Post-Consumer Content Type 6,6 Nylon	
Yarn Manufacturer	Universal	
Dye Method	100% Solution Dyed	
Dye Lots	Non-Mergeable	
Soil/Stain Protection	Protekt ^{2®}	
Preservative Protection	Intersept [®]	
	Imperial	Metric
Tufted Yarn Weight	23 oz/yd²,23 oz/yd²	780 g/m²
Machine Gauge	1/12 in	47.2 ends/10cm
Pile Height	0.15 in	3.8 mm
Pile Thickness	0.131 in	3.3 mm
Stitches	12.3 /in	48.5 ends/10cm
Pile Density	6,321 oz/yd³	236.3 g/m³
Size	19.69 in x 19.69 in	50cm x 50cm
Performance Specifications		
Flooring Radiant Panel	(ASTM E-648) Class 1	
Lightfastness	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's	
Static	(AATCC - 134) < 3.0 KV	
Dimensional Stability	AACHEN Din 54318 <.10%	
Traffic Classification	Severe	
Fiber Modification Ratio	1.7 to 1.9	
Preservative Efficacy	(AATCC 174 Parts 2&3) 99% Reduction/No Mold 7 Days (ASTM E-2471) Complete Inhibition	
Environmental Specifications		
Total Recycled Content	62%	
Recycled Content (Post Industrial)	59%	
Recycled Content (Post Consumer)	2%	
Indoor Air Quality	Green Label Plus #GLP0820	
Ingredients and Life Cycle Impacts	Environmental Product Declaration	
Other Environmental Claims	3rd Party Verified Carbon Neutral NSF/ANSI 140 Gold - Sustainability Assessment	
End of Life	Carpet to Carpet Recycling	
Technical Information		
Installation	See Interface Installation Guidelines online	
Maintenance	See recommended Interface Maintenance Guidelines online	
Reclamation	Recyclable through ReEntry $^{\! \rm B}$ - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)	
Warranty	15 Year Standard Carpet Warranty	
Standard Backing	GlasBac [®]	
Backing Options	GlasBac [®] , GlasBac [®] RE, CushionBac Renew™	
Tile Size Options	50cm x 50cm, 50cm x 1m	
Manufacturing Location	ISO 9001 & 14001 Certified facilities in Troup County, Georgia, United States	

May 18, 2018 Page 1 of 1