

TL49

GREENRAY
led lighting



PRODUCT DESCRIPTION

- Nuestros proyectores son ideales para brindar iluminación en tiendas, oficinas, vestíbulos, museos y galerías.
- Disponible en temperaturas cálida, neutra y fría.
- Construidas con los más altos estándares de calidad y cuentan con al menos 3 años de garantía limitada.
- Utilizan fuente de luz LED de alta potencia, gran eficacia.
- La luminaria es una fuente de luz conforme a RoHS, ambientalmente segura y no contiene mercurio
- El driver de corriente continua asegura alta eficiencia, vida útil prolongada, buena disipación de calor.
- Los proyectores pueden venir para riel, para empotrar o para adosar. (A,B,C, D)

PRODUCT SPECIFICATIONS

LED package: SMD 2835	Dimmable: Si *Configurable
Power Consumption: 15-45 $\pm$ 5% W	Material: Aluminio
Operation Voltage: 100 a 240V AC 50/60Hz	Fire rating: 94 VO
Efficacy: 95 lm/W	IP Rating: IP20
THD: <20%	Operating Temperature: - 25 °C + 50°C
PF: >0.9	Lifespan (L70): 40,000 horas
CRI: >80, >90	Light depreciation: < 30%
Power: 15, 30, 37, 45W	Beam Angle: 60°
	Warranty: 3 años



3 YEARS
WARRANTY



DIMMABLE



PIR
SENSOR



DALI



MOTION
SENSOR



ZIGBEE



EMERGENCY
MODULE

PRODUCT RANGE

Model	Voltage (V)	Power (W)	CCT (K)	Lumens (lm)	Efficacy (lm/W)	CRI	Angle (°)	Dimensions (AxBxC)
GRU-TL49-015L-D	100-240V 50/60HZ	15	3000-5500	1455	97	>80, >90	60°	319.5x42x195.5mm
GRU-TL49-030L-D	100-240V 50/60HZ	30	3000-5500	2850	95	>80, >90	60°	424.5x42x195.5mm
GRU-TL49-037L-D	100-240V 50/60HZ	37	3000-5500	3515	95	>80, >90	60°	529.5x42x195.5mm
GRU-TL49-045L-D	100-240V 50/60HZ	45	3000-5500	4050	90	>80, >90	60°	529.5x42x195.5mm

GRU	TL49	15	L	30	C/F	60°	N/D	MRV
GREENRAY	Track Light	Power	Series	Temperature CCT	Cleared / Frosted	Angle	Non dimmable / dimmable	100-240VAC
i.e: GRU-TL49-015L-30C-DMRV								

PRODUCT APPLICATION



CERTIFICATIONS

Green Ray LED Lightning products have certifications granted by international technological laboratories that guarantee the highest quality in terms of efficacy, efficiency, performance and consumption.

