



thrislington cubicles

uk +44 1244 520 677
usa +1 833 878 4747
dubai: +971 4387 1357

sales@thrislingtoncubicles.com
usprojects@thrislingtoncubicles.com
mideast@thrislingtoncubicles.com



ribbon high pressure laminate


product summary

Also available in:

- Acrylic
- Aluminium
- Veneer

ribbon high pressure laminate product summary

Ribbon Feature:	Ribbon Benefit:
Full aluminium framework, not visible from front elevation.	Gives strength to the system, whilst maintaining beautiful clean design.
Standard height of 2500mm (98 7⁄16") with 100mm (4") floor gap.	On many washrooms, the system can be taken close to the ceiling.
Floor gap can vary from 50mm (2") to 229mm (9")	Our bespoke design service allows individual design features on each individual washroom.
31mm (1 1⁄4") rebated doors to ensure flush finish.	Ensures zero sightlines.
Pivoted door.	No visible hinges, even on outward opening doors.
Self-closing hydraulic door closer.	Ensures door closes softly and beautifully, eliminating slamming.
Precision engineered stainless steel lock with flush face plate, hand turned in UK.	Our locks are designed by us and engineered for us, they cannot be bought off the shelf.
Lock designed to be opened using a closed fist.	Inclusive design and simple to use.
Lock locates into aluminium extrusion on closing side of the door.	Removes weak point of a face-fixed lock keep.
303 grade stainless steel hardware.	Toughness and resistance to oxidation.
Emergency release.	System can be opened quickly from outside.
Wide range of finishes available from various leading manufacturers.	Unlike competitors, Thrislington will work with a range of suppliers.
Core sourced from legal and sustainable sources.	Ensures the system is built to meet any modern washroom code.
10 year warranty.	Built to stand the test of time.
Please see website for current environmental policy.	Thrislington work constantly to improve environmental credentials as products update.



Standard version up to 2500mm (98 7⁄16") high with 100mm (4") floor gap.

Optional Extras

- LED Indicators
- Smart
- Structural Walls
- Hardware Finishes
- Framework Finishes
- Arc
- Fino Accessories



Warranty: 10 Years	Tested: 200,000 operations	Manufactured in: UK and USA	<div data-bbox="1534 135 1601 175"></div> <div data-bbox="1612 135 1971 175">thrislington cubicles</div>
<div data-bbox="152 347 712 371">K32 Specification: Ribbon High Pressure Laminate Cubicles</div> <div data-bbox="152 391 1267 494">Specification: Flush fronted, Doc-M compliant, cubicle system incorporating full aluminium framework, proprietary hydraulic closer, internal pivoting system and rebated doors ensuring zero sight lines. Overall cubicle height up to 2500mm (98 7⁄16") with 100mm (4") floor clearance as standard. Floor clearance can be varied between 50mm (2") to 229mm (9"). Supplied and installed with a 10-year warranty. All core materials are sourced from sustainable forests.</div> <div data-bbox="152 513 1245 590">Framework: Extruded aluminium framework, concealed to front of cubicles, with visible framework internally. Aluminium framework provides inherent strength. Architectural aluminium alloy 6063T6 with a 5-micron anodised finish and up to 70% recycled content. Aluminium headrail finished on external face in chosen material.</div> <div data-bbox="152 609 1252 740">Closing System: Doors soft-close by means of a proprietary hydraulic closer, which eliminates slamming and is designed specifically to fit within the structural aluminium headrail. Internal pivots ensure there are no visible external fixings even to open-out doors. Hydraulic closer, whether for inward or outward opening doors, incorporates a restrictor which comes into operation once a door is opened to 90 degrees, Hydraulic closer tested over a cycle of 200,000 operations, equating to a 10-year period in a medium use washroom. As an alternative, hydraulic closer can be factory set to fall open.</div> <div data-bbox="152 759 1258 863">Door: 31mm (1 ¼") finished thickness consisting of a 29mm (1 ⅙") ultra lightweight MDF core, edged all round and faced in chosen material. Hand lipped rebated doors ensure flush finish and zero sight lines. Concealed inserts within the door allow attachment to stainless steel pivots, with the top pivot being suspended from the structural aluminium headrail and the bottom pivot located onto a post fixed pivot bracket. Stainless steel lock rotates into the aluminium closing extrusion.</div> <div data-bbox="152 882 1270 959">Fascia: 63mm (2 ½") finished thickness consisting of a 12mm (½") moisture resistant MDF core panel, edged first and faced in chosen material, then attached to an aluminium framework. If fascia exceeds 150mm (5 7⁄8") it may need to be supported by a stainless steel foot.</div> <div data-bbox="152 978 1270 1109">Divider: 17mm (⅝") finished thickness consisting of a 15mm (⅜") moisture resistant chipboard core, edged top and bottom then faced in chosen material. Divider supported 100mm from the floor as standard, using a stainless steel foot, with height adjustment. Foot is fixed to the divider by extruded aluminium u-bracket, with stainless steel look finish. Fixed to the back wall using concealed zinc plated steel brackets with visible through-fixing heads. Attached at front to cubicle framework using M6 countersunk machine screws.</div> <div data-bbox="152 1128 1261 1313">Fittings: Precision engineered 303 grade brushed stainless steel fittings manufactured in the UK. Hand-turned, proprietary stainless steel lock complete with door buffer and external lock release facility, to allow access in an emergency. Lock is fixed through the door to the face plate for added strength. Lock designed to allow operation using a closed fist, ensuring inclusive design for users with reduced manual dexterity. Lock locates into aluminium framework, which eliminates the weak point of a face fixed lock keep. As a secondary measure to the emergency release facility in the faceplate, the lock finger contains a sacrificial hard nylon shear tip designed to break when put under undue force. Proprietary stainless steel buffered coat hook supplied as standard to all cubicles. Proprietary stainless steel pull handle supplied as standard to outward opening cubicles.</div> <div data-bbox="152 1332 775 1380">Available Finishes: 0.8mm high pressure laminate from a range of leading manufacturers.</div>			<div data-bbox="1400 363 2128 1313"></div>